



AICrNX Coated-Plain Shank



AICrNX Coated-Weldon Shank

### Variable Index, 4-Flute, Square & Corner Radius, 38° Helix

Cutter ø	Decimal Equiv	Flute Length	OAL	Corner Radius	Shank ø	AICrNX Coated	
						Plain Shank Part #	Weldon Shank Part #
1/2	.5000	1-1/4	3	.015	1/2	<a href="#">REV4351</a>	<a href="#">REV4352</a>
1/2	.5000	1-1/4	3	.030	1/2	<a href="#">REV4353</a>	<a href="#">REV4354</a>
1/2	.5000	1-1/4	3	.060	1/2	<a href="#">REV4355</a>	<a href="#">REV4356</a>
1/2	.5000	1-1/4	3	.090	1/2	<a href="#">REV4357</a>	<a href="#">REV4358</a>
1/2	.5000	1-1/4	3	.120	1/2	<a href="#">REV4359</a>	<a href="#">REV4360</a>
1/2	.5000	1-1/2	4	—	1/2	<a href="#">REV4361</a>	<a href="#">REV4362</a>
1/2	.5000	1-1/2	4	.030	1/2	<a href="#">REV4363</a>	<a href="#">REV4364</a>
1/2	.5000	1-1/2	4	.060	1/2	<a href="#">REV4365</a>	<a href="#">REV4366</a>
1/2	.5000	2	4	—	1/2	<a href="#">REV4367</a>	<a href="#">REV4368</a>
1/2	.5000	2	4	.030	1/2	<a href="#">REV4369</a>	<a href="#">REV4370</a>
1/2	.5000	2	4	.060	1/2	<a href="#">REV4371</a>	<a href="#">REV4372</a>
1/2	.5000	3	6	—	1/2	<a href="#">REV4373</a>	<a href="#">REV4374</a>
1/2	.5000	3	6	.030	1/2	<a href="#">REV4375</a>	<a href="#">REV4376</a>
1/2	.5000	3	6	.060	1/2	<a href="#">REV4377</a>	<a href="#">REV4378</a>
5/8	.6250	3/4	3	—	5/8	<a href="#">REV4379</a>	<a href="#">REV4380</a>
5/8	.6250	3/4	3	.030	5/8	<a href="#">REV4381</a>	<a href="#">REV4382</a>
5/8	.6250	1-5/8	3-1/2	—	5/8	<a href="#">REV4383</a>	<a href="#">REV4384</a>
5/8	.6250	1-5/8	3-1/2	.030	5/8	<a href="#">REV4385</a>	<a href="#">REV4386</a>
5/8	.6250	1-5/8	3-1/2	.060	5/8	<a href="#">REV4387</a>	<a href="#">REV4388</a>
5/8	.6250	1-5/8	3-1/2	.090	5/8	<a href="#">REV4389</a>	<a href="#">REV4390</a>
5/8	.6250	1-5/8	3-1/2	.120	5/8	<a href="#">REV4391</a>	<a href="#">REV4392</a>
5/8	.6250	2-1/4	5	—	5/8	<a href="#">REV4393</a>	<a href="#">REV4394</a>
5/8	.6250	2-1/4	5	.030	5/8	<a href="#">REV4395</a>	<a href="#">REV4396</a>
5/8	.6250	2-1/4	5	.060	5/8	<a href="#">REV4397</a>	<a href="#">REV4398</a>
5/8	.6250	3	6	—	5/8	<a href="#">REV4399</a>	<a href="#">REV4400</a>
5/8	.6250	3	6	.030	5/8	<a href="#">REV4401</a>	<a href="#">REV4402</a>
5/8	.6250	3	6	.060	5/8	<a href="#">REV4403</a>	<a href="#">REV4404</a>
3/4	.7500	1	3	—	3/4	<a href="#">REV4405</a>	<a href="#">REV4406</a>
3/4	.7500	1	3	.030	3/4	<a href="#">REV4407</a>	<a href="#">REV4408</a>
3/4	.7500	1-5/8	4	—	3/4	<a href="#">REV4409</a>	<a href="#">REV4410</a>
3/4	.7500	1-5/8	4	.030	3/4	<a href="#">REV4411</a>	<a href="#">REV4412</a>
3/4	.7500	1-5/8	4	.060	3/4	<a href="#">REV4413</a>	<a href="#">REV4414</a>
3/4	.7500	1-5/8	4	.090	3/4	<a href="#">REV4415</a>	<a href="#">REV4416</a>



Tolerances	Diameter	Shank	Radius
1/8" - 1/2"	+0.000, -0.002	-0.0001, -0.0004	+0.001, -0.001
5/8" - 1"	+0.000, -0.003	-0.0001, -0.0004	+0.001, -0.001



Speeds & Feeds pages 192 & 193.