



### Carbide Straight Flute Reamers (.3937-.4330)

Size	Decimal Equiv	# of Flutes	FL	OAL	Shank ø	Uncoated Part #
<b>10MM</b>	.3937	6	1-1/4	3-1/2	.3937	<a href="#">RR23475</a>
-	.3940	6	1-1/4	3-1/2	.3940	<a href="#">RR23476</a>
-	.3950	6	1-1/4	3-1/2	.3950	<a href="#">RR23477</a>
-	.3960	6	1-1/4	3-1/2	.3960	<a href="#">RR23478</a>
<b>X</b>	.3970	6	1-1/4	3-1/2	.3970	<a href="#">RR23479</a>
-	.3980	6	1-1/4	3-1/2	.3980	<a href="#">RR23480</a>
-	.3990	6	1-1/4	3-1/2	.3990	<a href="#">RR23481</a>
-	.4000	6	1-1/4	3-1/2	.4000	<a href="#">RR23482</a>
-	.4010	6	1-1/4	3-1/2	.4010	<a href="#">RR23483</a>
-	.4020	6	1-1/4	3-1/2	.4020	<a href="#">RR23484</a>
-	.4030	6	1-1/4	3-1/2	.4030	<a href="#">RR23485</a>
<b>Y</b>	.4040	6	1-1/4	3-1/2	.4040	<a href="#">RR23486</a>
-	.4050	6	1-1/4	3-1/2	.4050	<a href="#">RR23487</a>
-	.4060	6	1-1/4	3-1/2	.4060	<a href="#">RR23488</a>
<b>13/32</b>	.4062	6	1-1/4	3-1/2	.4062	<a href="#">RR23489</a>
-	.4070	6	1-1/4	3-1/2	.4070	<a href="#">RR23490</a>
-	.4080	6	1-1/4	3-1/2	.4080	<a href="#">RR23491</a>
-	.4090	6	1-1/4	3-1/2	.4090	<a href="#">RR23492</a>
-	.4100	6	1-1/4	3-1/2	.4100	<a href="#">RR23493</a>
-	.4110	6	1-1/4	3-1/2	.4110	<a href="#">RR23494</a>
-	.4120	6	1-1/4	3-1/2	.4120	<a href="#">RR23495</a>
<b>Z</b>	.4130	6	1-1/4	3-1/2	.4130	<a href="#">RR23496</a>
<b>10.5MM</b>	.4134	6	1-1/4	3-1/2	.4134	<a href="#">RR23497</a>
-	.4140	6	1-1/4	3-1/2	.4140	<a href="#">RR23498</a>
-	.4150	6	1-1/4	3-1/2	.4150	<a href="#">RR23499</a>
-	.4160	6	1-3/8	4	.4160	<a href="#">RR23500</a>
-	.4170	6	1-3/8	4	.4170	<a href="#">RR23501</a>
-	.4180	6	1-3/8	4	.4180	<a href="#">RR23502</a>
-	.4190	6	1-3/8	4	.4190	<a href="#">RR23503</a>
-	.4200	6	1-3/8	4	.4200	<a href="#">RR23504</a>
-	.4210	6	1-3/8	4	.4210	<a href="#">RR23505</a>
<b>27/64</b>	.4219	6	1-3/8	4	.4219	<a href="#">RR23506</a>
-	.4220	6	1-3/8	4	.4220	<a href="#">RR23507</a>
-	.4230	6	1-3/8	4	.4230	<a href="#">RR23508</a>
-	.4240	6	1-3/8	4	.4240	<a href="#">RR23509</a>
-	.4250	6	1-3/8	4	.4250	<a href="#">RR23510</a>
-	.4260	6	1-3/8	4	.4260	<a href="#">RR23511</a>
-	.4270	6	1-3/8	4	.4270	<a href="#">RR23512</a>
-	.4280	6	1-3/8	4	.4280	<a href="#">RR23513</a>
-	.4290	6	1-3/8	4	.4290	<a href="#">RR23514</a>
-	.4300	6	1-3/8	4	.4300	<a href="#">RR23515</a>
-	.4310	6	1-3/8	4	.4310	<a href="#">RR23516</a>
-	.4320	6	1-3/8	4	.4320	<a href="#">RR23517</a>
-	.4330	6	1-3/8	4	.4330	<a href="#">RR23518</a>

### Carbide Straight Flute Reamers (.4331-.4688)

Size	Decimal Equiv	# of Flutes	FL	OAL	Shank ø	Uncoated Part #
<b>11MM</b>	.4331	6	1-3/8	4	.4331	<a href="#">RR23519</a>
-	.4340	6	1-3/8	4	.4340	<a href="#">RR23520</a>
-	.4350	6	1-3/8	4	.4350	<a href="#">RR23521</a>
-	.4360	6	1-3/8	4	.4360	<a href="#">RR23522</a>
-	.4365	6	1-3/8	4	.4365	<a href="#">RR23523</a>
-	.4370	6	1-3/8	4	.4370	<a href="#">RR23524</a>
<b>7/16</b>	.4375	6	1-3/8	4	.4375	<a href="#">RR23525</a>
-	.4380	6	1-3/8	4	.4380	<a href="#">RR23526</a>
-	.4385	6	1-3/8	4	.4385	<a href="#">RR23527</a>
-	.4390	6	1-3/8	4	.4390	<a href="#">RR23528</a>
-	.4400	6	1-3/8	4	.4400	<a href="#">RR23529</a>
-	.4410	6	1-3/8	4	.4410	<a href="#">RR23530</a>
-	.4420	6	1-3/8	4	.4420	<a href="#">RR23531</a>
-	.4430	6	1-3/8	4	.4430	<a href="#">RR23532</a>
-	.4440	6	1-3/8	4	.4440	<a href="#">RR23533</a>
-	.4450	6	1-3/8	4	.4450	<a href="#">RR23534</a>
-	.4460	6	1-3/8	4	.4460	<a href="#">RR23535</a>
-	.4470	6	1-3/8	4	.4470	<a href="#">RR23536</a>
-	.4480	6	1-3/8	4	.4480	<a href="#">RR23537</a>
-	.4490	6	1-3/8	4	.4490	<a href="#">RR23538</a>
-	.4500	6	1-3/8	4	.4500	<a href="#">RR23539</a>
-	.4510	6	1-3/8	4	.4510	<a href="#">RR23540</a>
-	.4520	6	1-3/8	4	.4520	<a href="#">RR23541</a>
<b>11.5MM</b>	.4528	6	1-3/8	4	.4528	<a href="#">RR23542</a>
-	.4530	6	1-3/8	4	.4530	<a href="#">RR23543</a>
<b>29/64</b>	.4531	6	1-3/8	4	.4531	<a href="#">RR23544</a>
-	.4540	6	1-3/8	4	.4540	<a href="#">RR23545</a>
-	.4550	6	1-3/8	4	.4550	<a href="#">RR23546</a>
-	.4560	6	1-3/8	4	.4560	<a href="#">RR23547</a>
-	.4570	6	1-3/8	4	.4570	<a href="#">RR23548</a>
-	.4580	6	1-3/8	4	.4580	<a href="#">RR23549</a>
-	.4590	6	1-3/8	4	.4590	<a href="#">RR23550</a>
-	.4600	6	1-3/8	4	.4600	<a href="#">RR23551</a>
-	.4610	6	1-3/8	4	.4610	<a href="#">RR23552</a>
-	.4620	6	1-3/8	4	.4620	<a href="#">RR23553</a>
-	.4630	6	1-3/8	4	.4630	<a href="#">RR23554</a>
-	.4640	6	1-3/8	4	.4640	<a href="#">RR23555</a>
-	.4650	6	1-3/8	4	.4650	<a href="#">RR23556</a>
-	.4660	6	1-3/8	4	.4660	<a href="#">RR23557</a>
-	.4670	6	1-3/8	4	.4670	<a href="#">RR23558</a>
-	.4680	6	1-3/8	4	.4680	<a href="#">RR23559</a>
<b>15/32</b>	.4688	6	1-3/8	4	.4688	<a href="#">RR23560</a>

Carbide Reamers



Speeds, feeds & tech info pages 497-498.

Tolerances	Diameter	Shank
All Sizes	+0.003, -0.000	+0.003, -0.002

