




## HSK63A Facemill Holders



- Pilot diameter is sized for precision fit with cutter
- Face perpendicular to center line within .0002"
- Removable/replaceable drive keys are standard
- Fine thread locking screw is included
- Less tool wear and replacement means less scrap



<b>HSK63A Facemill Holders</b>					
Taper	Size A	Gage Length (B)	C	L	Part #
HSK63A	3/4	1.75	1.69	1.02	<a href="#">RHSK63ASM0750175</a>
HSK63A	3/4	4.00	1.69	1.02	<a href="#">RHSK63ASM0750400</a>
HSK63A	1	1.88	2.06	1.02	<a href="#">RHSK63ASM1000188</a>
HSK63A	1	4.00	2.06	1.02	<a href="#">RHSK63ASM1000400</a>
HSK63A	1-1/4	2.50	2.75	1.02	<a href="#">RHSK63ASM1250250</a>
HSK63A	1-1/4	4.00	2.75	1.02	<a href="#">RHSK63ASM1250400</a>
HSK63A	1-1/2	2.75	3.81	1.02	<a href="#">RHSK63ASM1500275</a>
HSK63A	1-1/2	4.00	3.81	1.02	<a href="#">RHSK63ASM1500400</a>

<b>Facemill Holder Replacement Lock Screws</b>							
Holder Size	Size A	B	C	D	Photo	Dimensions	Part #
3/4	.875	3/8-24	.63	.37			<a href="#">RSMLS0750</a>
1	1.188	1/2-20	.81	.37			<a href="#">RSMLS1000</a>
1-1/4	1.500	5/8-18	.94	.50			<a href="#">RSMLS1250</a>
1-1/2	1.875	3/4-16	1.13	.50			<a href="#">RSMLS1500</a>

<b>Facemill Holder Replacement Drive Keys</b>					
Holder Size	Size A	B	Photo	Dimensions	Part #
3/4	5/16	5/32			<a href="#">RSMDK0750</a>
1	3/8	3/16			<a href="#">RSMDK1000</a>
1-1/4	1/2	1/4			<a href="#">RSMDK1250</a>
1-1/2	5/8	5/16			<a href="#">RSMDK1500</a>

Note: Drive keys are in line with drive slot.

<b>HSK63A Coolant Accessories</b>		
HSK63A Coolant Tube	HSK63A Coolant Tube Plug	HSK63A Coolant Tube Wrench
<a href="#">RHSK63ACT</a>	<a href="#">RHSK63AHP</a>	<a href="#">RHSK63ATW</a>