

## Micro 4-Flute



Uncoated



AlTiN Coated

### 4-Flute, Square End, Extra Long Reach, Stub Flute, 30° Helix (.0938-.1250)

Cutter ø	Flute Length	XD LOC	OAL	Reach Length	XD Reach	Shank ø	Uncoated Part #	AlTiN Coated Part #
.0938	.281	3	2	.590	6	1/8	<a href="#">RET8882</a>	<a href="#">RET8883</a>
.0950	.285	3	1-1/2	.625	6	1/8	<a href="#">RET8884</a>	<a href="#">RET8885</a>
.0950	.285	3	2	.750	8	1/8	<a href="#">RET8886</a>	<a href="#">RET8887</a>
.1000	.300	3	1-1/2	.625	6	1/8	<a href="#">RET8888</a>	<a href="#">RET8889</a>
.1000	.300	3	2	.750	7	1/8	<a href="#">RET8890</a>	<a href="#">RET8891</a>
.1094	.328	3	2	.590	5	1/8	<a href="#">RET8892</a>	<a href="#">RET8893</a>
.1100	.330	3	2	.750	7	1/8	<a href="#">RET8894</a>	<a href="#">RET8895</a>
.1250	.375	3	2	.590	5	1/8	<a href="#">RET8896</a>	<a href="#">RET8897</a>



Speeds & Feeds page 217.

Tolerances	Diameter	Shank
All Sizes	+0.000, -0.001	+0.000, -0.0003