
CAT40 Toolholders

CAT40 & Straight Shank ER25 Collet Chucks

(Balanced to G2.5@18,000 RPM)

- · Small diameter nose well-suited for working in close quarters
- Increased flexibility for milling, drilling, and reaming
- Flush precision collet nut, grips tool close to cutting edge for accuracy and rigidity
- Concentric to .0002" TIR puts tool precisely on spindle center line
- AT3 or better shank taper allows for accurate, rigid toolholder-tospindle mount
- Wide range collets reduce collet and toolholder inventories
- Fully ground flange and V-groove is easy on tool changers for less spindle and changer maintenance
- Through spindle coolant standard
- ER25 Collets found on pages 606-607.



CAT40 ER25 Collet Chucks								
Capacity	Taper	А	Gage Length (B)	D	L	Max. Nosepiece Torque	Part #	
.040629	CAT40	1.64	2.50	3.00	1.38	42 ft lbs	RC4ER25250	
.040629	CAT40	1.64	4.00	3.50	1.38	42 ft lbs	RC4ER25400	
.040629	CAT40	1.64	6.00	3.50	1.38	42 ft lbs	RC4ER25600	

ER25 Straight Shank Collet Extension Α В D L Photo Dimensions Part # \boxtimes Α 7.5 5.5 **RSSER25750** 1.64 1.00 t_p

ER25 Parts & Accessories								
Description	Photo	Dimensions	Part #					
ER25 Replacement Nosepiece	Õ	1.64	<u>RER25NPA</u>					
ER25 Collet Wrench [†]	Å	E E	<u>RER25W</u>					
ER25 Stop Screw		Irehaw Sed	RER25SS					
ER25 Stop Screw Coolant Thru		L.H. Coolaat Threads Passage (913 x 1.5)	RER25SSC					

[†]Required for assembly.