CAT50 Toolholders






CAT50 & Straight Shank ER20 Collet Chucks

(Balanced to G2.5@15,000 RPM)

- Small diameter nose well-suited for working in close quarters
- Increased flexibility for milling, drilling, and reaming
- Flush precision collet nut, grips tool close to cutting edge for accuracy and rigidity
- Concentric to .0002" TIR puts tool precisely on spindle center line
- AT3 or better shank taper allows for accurate, rigid toolholder-to-spindle mount
 - Wide range collets reduce collet and toolholder inventories
- Fully ground flange and V-groove is easy on tool changers for less spindle and changer maintenance
- Through spindle coolant standard
- ER20 Collets found on pages 604-605.



CAT50 ER20 Collet Chucks							
Capacity	Taper	А	Gage Length (B)	D	L	Max. Nosepiece Torque	Part #
.040511	CAT50	1.38	4.00	3.50	1.38	36 ft Ibs	RC5ER204000
.040511	CAT50	1.38	6.00	3.50	1.38	36 ft lbs	RC5ER206000
.040511	CAT50	1.38	8.00	3.50	1.38	36 ft lbs	RC5ER208000

ER20 Straight Shank Collet Extension							
А	В	D	L	Photo	Dimensions	Part #	
1.38	7.0	1.00	5.8			<u>RSSER20700</u>	

ER20 Parts & Accessories							
Description	Photo	Dimensions	Part #				
ER20 Replacement Nosepiece	Õ	1.38	RER20NPA				
ER20 Collet Wrench [†]	\mathbf{x}	6.50	<u>RER20W</u>				
ER20 Stop Screw		L.H. Therado (M3+x1.5)	RER20SS				
ER20 Stop Screw Coolant Thru			RER20SSC				

[†]Required for assembly.