



Oxide

HSS, Taper Shank, 118° Point (.8594-2.0000)					
Drill Size	Decimal Equiv	Flute Length	OAL	Shank ø	Oxide Part #
55/64	.8594	6-1/8	10-3/4	#3	RD42655
7/8	.8750	6-1/8	10-3/4	#3	RD42656
57/64	.8906	6-1/8	10-3/4	#3	RD42657
29/32	.9062	6-1/8	10-3/4	#3	RD42658
59/64	.9219	6-1/8	10-3/4	#3	RD42659
15/16	.9375	6-1/8	10-3/4	#3	RD42660
61/64	.9531	6-3/8	11	#3	RD42661
31/32	.9688	6-3/8	11	#3	RD42662
63/64	.9844	6-3/8	11	#3	RD42663
1	1.0000	6-3/8	11	#3	RD42664
1-1/64	1.0156	6-1/2	11-1/8	#3	RD42665
1-1/32	1.0312	6-1/2	11-1/8	#3	RD42666
1-3/64	1.0469	6-5/8	11-1/4	#3	RD42667
1-1/16	1.0625	6-5/8	11-1/4	#3	RD42668
1-5/64	1.0781	6-7/8	12-1/2	#4	RD42669
1-3/32	1.0938	6-7/8	12-1/2	#4	RD42670
1-7/64	1.1094	7-1/8	12-3/4	#4	RD42671
1-1/8	1.1250	7-1/8	12-3/4	#4	RD42672
1-9/64	1.1406	7-1/4	12-7/8	#4	RD42673
1-5/32	1.1562	7-1/4	12-7/8	#4	RD42674
1-11/64	1.1719	7-3/8	13	#4	RD42675
1-3/16	1.1875	7-3/8	13	#4	RD42676
1-13/64	1.2031	7-1/2	13-1/8	#4	RD42677
1-7/32	1.2187	7-1/2	13-1/8	#4	RD42678
1-1/4	1.2500	7-7/8	13-1/2	#4	RD42680
1-5/16	1.3125	8-5/8	14-1/4	#4	RD42684
1-3/8	1.3750	8-7/8	14-1/2	#4	RD42688
1-7/16	1.4375	9-1/8	14-3/4	#4	RD42692
1-1/2	1.5000	9-3/8	15	#4	RD42696
1-9/16	1.5625	9-5/8	16-5/8	#5	RD42702
1-5/8	1.6250	10	17	#5	RD42706
1-11/16	1.6875	10-1/8	17-1/8	#5	RD42710
1-3/4	1.7500	10-1/8	17-1/8	#5	RD42714
1-13/16	1.8125	10-1/8	17-1/8	#5	RD42718
1-7/8	1.8750	10-3/8	17-3/8	#5	RD42722
1-15/16	1.9375	10-3/8	17-3/8	#5	RD42726
2	2.0000	10-3/8	17-3/8	#5	RD42730

