



High Performance Coolants and Cutting Oils

- Provides outstanding performance
- Low odor
- Long lasting
- High quality standards results in consistent reliable performance
- No disproportionate depletion of additives so none are required
- Safe for people who use it and for the environment
- Reach compliant
- Available in 5 gallon pails, 55 gallon drums or totes. When ordering, specify quantity in gallons, 5 gallon minimum



Coolants							
Part #	Material Compatibility						
	Aluminum Alloys	Carbon Steel	Cast Iron*	Nickel Alloys	Stainless Steel	Titanium	Brass
RC3000	●●	●●	●	●●	●●	●	●
RC3500	●●	●●	●	●●	●●	●	●
RC3750	●	●●	●●	●	●	●	●

● = Recommended ●● = Highly Recommended

* As with all magnesium, extreme caution must be maintained when using water based fluids

Cutting/Machining Oils									
Part #	Stock Diameter			Material Compatibility					
	<0.25"	0.25-0.75"	>0.75"	Brass	Carbon Steel	Copper	Nickel Alloys	Stainless Steel	Titanium
RO1722	●	●●	●●	●●	●●	●●	●	●●	●
RO1710	●●	●●	●	●●	●●	●●	●	●●	●

● = Recommended ●● = Highly Recommended

Grinding Oil									
Part #	Grind Type			Material Compatibility					
	Flute	Edge	Surface Profile	Carbide	Ceramic	Cement	CBN	PCD	HSS
RG17	●●	●●	●●	●●	●●	●●	●●	●●	●●

● = Recommended ●● = Highly Recommended

Machine Cleaner	
Part #	Description
RCMC3000	Sump Cleaner For System Clean Out Prior To Charge Up

*See page 630 for mixing ratios.

Mixing Ratios & Accessories

Coolant Concentration/Mixing Ratios					
Part #	Actual %*	General Purpose Machining		Heavy Machining	
		Start up	Top Off	Start up	Top Off
RC3000	RR x 1.0	10% mixing ratio = 10 RR	6% mixing ratio = 5 RR	14% mixing ratio = 10 RR	8% mixing ratio = 5 RR
RC3500	RR x 4.2	10% mixing ratio = 2.5 RR	6% mixing ratio = 1.5 RR	14% mixing ratio = 3 RR	8% mixing ratio = 2 RR
RC3750	RR x 3.3	6% mixing ratio = 3.3 RR	2% mixing ratio = 1.5 RR	10% mixing ratio = 4 RR	3% mixing ratio = 2 RR

*RR = Refractometer Reading



Basic Optical Refractometer

- Refractometer range 0-32 Brix
- Prism aperture lets in a lot of light
- Diamond-knurled sleeve for good gripping
- Comfortable eyepiece with adjustable focus for easy reading
- Auto temperature compensation for shop areas with varying temperature
- Average use accuracy range
- Carrying case with sampler included

Basic Optical Refractometer					
Part #	Brix Scale	Numbered Graduation	Accuracy	Weight	Dimensions
OPT32	0-32	Fifths	± .20%	9.3 oz	1.50" x 7" long



Flat Belt Oil Skimmer


- 1" Wide Belt Skimmers for Use with Metalworking Coolants and Wastewater Applications.
- 5" Belt Reach, flat polyurethane belt
- Steel stabilizer bar holds tail pulley in place
- Dependable, quiet permanent magnet motor
- Choice of 1 quart (ltr) or 1 gallon (4 ltrs) per hour
- Small size - fits almost anywhere
- 115V, single-phase 60 Hz
- 1 year warranty - 90 days on belts

Flat Belt Oil Skimmer			
Part #	Type	Reach	Collection Rate
37802	Flat	5"	1 quart (ltr) or 1 gallon (4 ltrs) per hour



Economy Mixers


- This economy mixer properly mixes coolant emulsions and maintains a consistent concentration for increased sump and tool life
- The design of the economy mixer (see diagram at right) enables it to have a high degree of reliability and precision
- 14 metering tips for specific ratios
- Maximum viscosity of 500 SUS
- 30 day warranty
- 48" discharge tube included (max length for delivery)



Economy Mixers

Part #	GPM	Mixing Range %*		Max. Delivery	Range PSI	Fittings, NPT		Application
		Low	High			In	Out	
MIX05120	4.8	.25	22.2	48"	25-75	3/4" GHT	1/2" NPT	Barrel
MIX03725	3.0	0	25.0	40"	25-75	3/8" GHT	1/2" NPT	Barrel

* Economy mixer is supplied with 14 various size tips within above range.



Mixing Pump

- Perfectly mixed coolant at EVERY use
- Delivers mix through hose or conduit right to your machine
- No need to verify concentration once initially determined
- Compact with few moving parts
- Can be permanently mounted to wall
- Maximum viscosity of 700 SUS
- 800' lateral max delivery, 20' vertical max delivery
- One year warranty with purchase of prepump water filter (#MIXPPX75)
- Units available for other wall mount configurations

HOW THE PUMP WORKS: Your coolant is drawn in through the bottom port (A) and metered by the adjustable screw (B) for a constant amount of water being drawn in through the fitting (C) on the other side. The entire arm (D) moves back and forth so that your coolant is being injected into the water stream. The mixing occurs at the exit fitting (E), and proceeds to your coolant sump. You can watch what is being drawn in the clear coolant block, and you know the unit is working perfectly by seeing the draw arm moving.

Mixing Pump

Part # ¹	GPM	Mixing Range %		Mixing Ratios*		Max. Delivery ²	Range PSI	Fittings, NPT		Application ³
		Low	High	Low	High			In	Out	
MIXPP518	7	1.4	12.3	1:71	1:8	800'	10-75	3/4"	3/4"	Pail, Barrel, Tote

¹ For wall mount configuration, add "(VM)" to end of part number

² The proportioning pump can also pump the mixture a vertical distance of 20' utilizing a pressure regulating valve

³ Unit is supplied with intake hose to meet this container type

Mixing Pump Accessories

Part #	Description
MIXPPX75	Prepump water filter for proportioning pump protection, 20µ (required to maintain warranty)
MIXXWL.1	Water limiter for proportioning pump protection
MIXXPRV.1	Pressure regulating valve (for applications with vertical delivery, ball valve discharge, or viscosities above 500 SUS)